

EntryRAE



Key Features

- Reliable, self-cleaning VOC detector
- Also includes CO, H₂S, LEL and O₂ sensors
- Simple to operate
- Easy to calibrate
- Durable, weather-resistant rubber body
- Datalogging included - and automatic
- Big display with auto-backlight
- Loud alarm
- Bright red flashing LED alarm
- Up to 16-hours of continuous operation
- Interchangeable Lithium-ion and alkaline battery packs
- Charging cradle doubles as an external battery charger

Confined Space Entry Monitor

The typical confined space monitor measures oxygen, combustibles, carbon monoxide and hydrogen sulfide. Will it keep you safe in today's industrial environment? No. When doing confined space work today, you need the added broadband protection of a PID.

The EntryRAE is a 4-gas monitor, plus photoionization (PID) detection. Reliable, easy to operate, and simple to calibrate, the EntryRAE delivers added protection without added complexity.

Simple, Modular, Durable PID

Our plug & play, self-cleaning (patented) PID is the most reliable and durable PID available today.

Why PID?

Typical 4-gas monitors do not detect volatile organic compounds (VOCs). VOCs are combustible, and often toxic at levels far below 10% LEL. They are commonly found in:

- Fuels, oils, degreasers
- Industrial cleaners
- Heat transfer fluid
- Solvents, paints
- Plastics, resins, adhesives
- Pesticides and herbicides

These are common industrial compounds you find in - or bring into - a confined space. LEL sensors can be poisoned by common chemicals including:

- Silicone compounds
- Lead compounds
- Sulfur compounds
- Phosphates

Just a few parts-per-million of these compounds can degrade an LEL sensor.

A PID detects VOCs

A PID is a reliable backup for your LEL sensor. Combine a PID and a 4-gas monitor and you have true protection from the unexpected.

Applications

- Refineries
- Chemical processing
- Water & wastewater facilities
- Semiconductor manufacturing
- Rail car and tank truck cleaning
- Resin and nylon production
- Underground storage
- Sewer entries
- Cable vaults
- Agriculture

Monitor only includes

- Monitor
- CO, H₂S, LEL and O₂ sensors
- Lithium-ion rechargeable battery
- Alkaline battery adapter
- 5 external filter
- Charging cradle
120 V wall charger, US plug,
or 230 V wall charger, Euro plug
- ProRAE Studio software package
- Computer interface cable
RS232 to RS232 with USB adapter
- User manual
- Shipping case

Optional CSK II Calibration Kit

- Hard transport case with pre-cut foam
- Sampling wand with 15 feet (3 meters) of self-coiling Teflo[®] tubing
- Toolkit
- Four-gas mix – 34 L (50% LEL, 20.9% O₂, 10 ppm H₂S, 50 ppm CO), regulator
- Isobutylene – 34 L (100 ppm, balance air), regulator
- Regulators and tubing

Truck Mount (Accessory):

- Cradle attachment for mounting on a wall
- 12 V adapter

AutoRAE Docking Station (Accessory)

- Automated bump test and calibration system
- Drop-in, push-button operation

Sensor Specifications

Sensor	Range	Resolution
PID	0-999 ppm VOC	1 ppm VOC
Oxygen	0-30.0%	0.1%
Combustible Gases	0-100% LEL 0-5% Volume	1% LEL 1% Volume
Carbon Monoxide	0-500 ppm	0-500 ppm
Hydrogen Sulfide	0-100 ppm	1 ppm

Technical Specification	
Size:	5.9"L x 3.3"W x 1.9"H (15 x 8.3 x 4.8 cm) without clip
Weight:	20 oz (567 g) with battery and clip
Sensors:	5 sensors: <ul style="list-style-type: none"> • Protected catalytic bead for combustible gases (LEL) • Electrochemical sensors for oxygen (O₂) and hydrogen sulfide (H₂S) and carbon monoxide (CO) • Modular photoionization detector for broadband detection of VOCs using 10.6 eV lamp
Battery:	<ul style="list-style-type: none"> • Drop-in rechargeable Li-ion battery pack • Standard alkaline battery adapter • Charging cradle doubles as external battery charger
Operating Hours:	16 hours continuous with Li-ion (typical), 12 hours with alkaline
Display Graphic:	Large 1.4" x 1.8" (3.5 x 4.5 cm) display with automatic back-lighting in dim light or alarm condition
Keypad :	Three-button operation
Direct Readout:	Instantaneous for 5 values: <ul style="list-style-type: none"> • Oxygen as percentage by volume • Combustible gas as percentage of lower explosive limit (LEL), percentage by volume • VOCs, CO and H₂S as parts per million • TWA and STEL values for VOCs, CO and H₂S • High and low values for all gases
Alarms:	<ul style="list-style-type: none"> • Audible (95 dB at 30 cm), visible, and vibration • High: 3 beeps and flashes per second • Low: 2 beeps and flashes per second • STEL and TWA: 1 beep and flash per second • Low battery displays empty battery symbol, 1 beep per minute
EMI/RFI:	Highly resistant to EMI / RFI. Compliant with EMC Directive 89/336/EEC
IP Rating:	IP-55: protected against dust, protected against low pressure jets of water from all directions
Communication:	PC to monitor via RS232 with USB adapter
Calibration:	Two-point field calibration for zero and span gas
Sampling Pump:	Built-in pump, 500 cc per minute flow rate
Low Flow Alarm:	Auto shut-off at low flow condition
Hazardous Area Approval:	UL Class 1 Division 1, Groups A, B C, D T3C. CSA pending, ATEX pending
Temperature:	-4° to 113°F (-20° to 45°C)
Humidity:	0% to 95% relative humidity (non-condensing)
Attachments:	Stainless steel alligator clip (installed), wrist strap
Warranty:	Lifetime on non-consuming components (per RAE Standard Limited Warranty) 2 years for O ₂ , LEL and CO, and H ₂ S sensors 1 year for PID 1 year for pump and battery

*Ongoing projects to enhance our products means that these specifications are subject to change.

Casella CEL

Regent House, Wolsley Road, Kempston, Bedford, MK42 7JY, United Kingdom
Tel: +44 (0) 1234 844100 Fax: +44 (0) 1234 841490 Email: info@casellacel.com Web: www.casellameasurement.com

SM11004 v 1.0